

AquaMatic[®] Valve VAV

This product is manufactured in the United States of foreign and domestic parts.

Features & Benefits

- Engineered for extended cycle life in high-use air applications
- Large seat opening and high lift-disc for higher flow rates at a lower pressure loss
- Separate flow and control chambers permit positive closing without springs; and only nominal cost for spring assist opening for low-pressure and selfdraining applications
- Cost-effective solution both in initial cost, as well as lifetime maintenance expenses
- Separate diaphragm chambers protects the diaphragm from the flow stream, while allowing the valve to be serviced in-line
- Constructed of cast iron, brass, stainless steel and Nitrile elastomer components, giving an unparalleled service life
- 3/4-inch through 3-inch threaded (N.P.T. or B.S.P.); 3-inch through 4-inch flanged drilled in accordance with ASA16.1 class 125, or BSP4504

Accessories & Options

- Seal and diaphragm materials available
- Handles liquid and gases
- Adaptable to wide variety of control devices
- Spring assist (open or closed)
- Position indicator
- Limit stop for adjustable flow rate control
- High temperature service

16605 West Victor Rd. New Berlin, WI 53151 | P: 262-326-0100 | www.aq-matic.com | techsupport@aq-matic.com

© 2016 AQ Matic Valve and Controls Company, Inc. All rights reserved.

All AQ Matic trademarks and logos are owned by AQ Matic or its affiliates. All other registered and unregistered trademarks and logos are the property of their respective owners. Because we are continuously improving our products and services, AQ Matic reserves the right to change specifications without prior notice. AQ Matic is an equal opportunity employer.

