
Т			0					
ITEM NO	PART NO	DESCRIPTION		531 QTY	534 QTY	535 QTY	537 QTY	UNITS
1	-	NORMALLY OPEN K53X	VALVE	1	1	1	1	EACH
2	1071941	CONNECTOR, 1/4 MNPT	X 1/4T	-	-	1	1	EACH
3	1078767	CONNECTOR, 1/8 MNPT	X 1/4T	1	1	-	-	EACH
4	1078770	FITTING, ELBOW, 1/4NP	T X 1/4T	-	-	1	1	EACH
5	1071937	FITTING, ELBOW, 1/8NP	T X 1/4T	1	1	-	-	EACH
6	1071936	TUBING, POLY 1/4" O.D.	X .035	9	12	14	16	INCHES

В

Α



Δ

DRILL AND TAP BOSS #1 1/8" NPT FOR 531 & 534 1/4" NPT FOR 535 & 537

(REFERENCE DRAWING - OSMONICS# AG-530-2)

		REV	ECN
		A	1248
		B	1696
	(535 S	5HO	WN
	/		
	//		
\frown	//		
(6)			
\smile			X
· · · · · · · · · · · · · · · · · · ·		1 1/	
			$\langle \rangle$
		K	$\langle \rangle$
		"	
		N	
\frown			
(4)			
	\sim		
			//
		11	
	- 1	\prec	
		$\langle \langle \rangle$	
			H
THE C	OMPONENT OR PRODU	UT DESCR	IDED IN

THIS DOCUMENT IS SOLELY THE PROPERTY OF AQ-MATIC REPRODUCTION, USE DISCLOSURE, OR TRANSMISSION OF THIS DOCUMENT OR DETAILS CONTAINED HEREIN, IN PART OR IN WHOLE, IS PROHIBITED WITHOUT THE WRITTEN CONSENT OF AQ-MATIC ENGINEERING. THIS DOCUMENT AND	THIRD ANGLE PROJECTION			
ANY COPIES SHALL BE RETURNED TO AQ-MATIC UPON WRITTEN REQUEST.	APPROVALS	DATE		
INTERPRET DIMENSIONS AND TOLERANCES PER ASME Y14.5M -1994	DRAWN PMJ	4/14/2020	DES	
UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES [mm]	CHECKED BY			
CORNER FILLETS R.005020 [.127508] TOLERANCES: ANGLES: +1°			SIZE	
1 PLACE .X: ± .100 [2.54]	APPROVED			
2 PLACE .XX: ± .010 [0.3] 3 PLACE .XXX: ± .005 [0.13]			SC/	

